

# SPRINKLER CEVI

TECHNICAL SPECIFICATIONS
Roll Grooved
FM approved
UL/C-UL Listed
NFS certified
NFS certified
Selection of Schedule 7, Schedule 10, Schedule 30/40, Easy Flow - Light Wall
Tight tolerances
Consistent roundness
Consistent wall thickness
Consistent straightness
Weldable
Pressure tested
Reliable high steel quality
Galvanised or shop primer coated black, red (RAL 3000)
CE, PED Certified
ASTM A795 and ASTM A53 Production standards

	Dimenzija (mm)	Dimenzija (inch)	Debljina zida	Pocinkovane		FM
				Kg/m	kg/m	
Easy Flow Light Wall	33,7	1"	2	1,56	1,62	x
	33,7	1"	2,6	1,99	2,06	x
	42,4	1 1/4"	2	1,99	2,06	x
	42,4	1 1/4"	2,3	2,27	2,35	x
	42,4	1 1/4"	2,6	2,55	2,64	x
	48,3	1 1/2"	2	2,28	2,36	x
	48,3	1 1/2"	2,6	2,93	3,03	x
	60,3	2"	2	2,88	2,98	x
	60,3	2"	2,9	4,1	4,25	x
	76,1	2 1/2"	2,18	3,97	4,11	x
	76,1	2 1/2"	2,9	5,23	5,42	x
	88,9	3"	2,36	4,04	5,21	x
	88,9	3"	3,2	6,76	7	x
	114,3	4"	2,6	7,16	7,41	x
	114,3	4"	3,6	9,83	10,17	x
139,7	5"	3,4	11,43	11,83	x	

	DN	Dimenzija (mm)	Dimenzija (inch)	Debljina zida (mm)	Kg/m	UL	FM
SCH 10	20	26,7	3/4"	2,11	1,28	x	
	25	33,4	1"	2,77	3,09	x	x
	32	42,2	1 1/4"	2,77	2,69	x	x
	40	48,3	1 1/2"	2,77	3,11	x	x
	50	60,3	2"	2,77	3,93	x	x
	65	73	2 1/2"	3,05	5,26	x	x
	80	88,9	3"	3,05	6,46	x	x
	90	101,6	3 1/2"	3,05	7,41	x	x
	100	114,3	4"	3,05	8,37	x	x
	125	141,3	5"	3,4	11,58	x	x
	150	168,3	6"	3,4	13,85	x	x
	200	219,1	8"	3,76	19,97	x	x
	250	273,1	10"	4,19	27,78	x	x
	SCH 30/40	15	21,3	1/2"	2,77	1,27	x
20		26,7	3/4"	2,87	1,69	x	
25		33,4	1"	3,38	2,5	x	x
32		42,2	1 1/4"	3,56	3,39	x	x
40		48,3	1 1/2"	3,68	4,05	x	x
50		60,3	2"	3,91	5,45	x	x
65		73	2 1/2"	5,16	8,64	x	x
80		88,9	3"	5,49	11,29	x	x
90		101,6	3 1/2"	5,74	13,58	x	x
100		114,3	4"	6,02	16,09	x	x
125		141,3	5"	6,55	21,79	x	x
150		168,3	6"	7,11	28,29	x	x
200		219,1	8"	7,04	36,82	x	x
250		273	10"	7,8	51,05	x	x